

Description

Corrosion resistant steel length: 1-1/32in., grip: 9/16in., thread: 10-32, countersunk, flat head, machine screw, structural

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

MS24694-C58

SKU / Model:	MS24694C58
Minimum Qty (MOQ):	100
NSN:	5305-00-900-3254
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS24694C58 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.437 Inches Minimum And 0.516 Inches Maximum
Fastener Length:	1.015 Inches Minimum And 1.062 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.327 Inches Minimum And 0.385 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	85000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Corrosion Resisting
Screw Material Document And Classification:	Qq-s-763,300 Series Fed Spec Single Material Response Or 66,300 Series Fed Std Single Material Response Or Comp 16-18 Or 18-8 Assn Std Single Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24694C58> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.