

P/N MS24694C67

Description

Fastener Length: 1-5/8", Thread: 10-32, Thread Length: 13/32",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

MS24694-C67

SKU / Model: MS24694C67

Minimum Qty (MOQ): 25

NSN: 5305-00-824-2014

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N MS24694C67 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.407 Inches Minimum
Fastener Length:	1.578 Inches Minimum And 1.625 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.327 Inches Minimum And 0.385 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	85000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 301 Or Steel Comp 302 Or Steel Comp 302b Or Steel Comp 303 Or Steel Comp 303 Plus X Or Steel Comp 303se Or Steel Comp 304 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 308 Or Steel Comp 309 Or Steel Comp 309s Or Steel Comp 310 Or Steel Comp 310s Or Steel Comp 314 Or Steel Comp 316 Or Steel Comp 316l Or Steel Comp 317 Or Steel Comp 321 Or Steel Comp 323 Or Steel Comp 324 Or Steel Comp 347 Or Steel Comp 348 Or Steel Comp 385
Screw Material Document And Classification:	66 Fed Std Single Material Response
Screw Surface Treatment:	Passivate
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS24694C67 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.