

Description

Length: 1 27/32", Thread: 10-32, flat countersunk head, structural, corrosion resistant steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS24694C71
Minimum Qty (MOQ):	5
NSN:	5305-00-824-2010
Schedule B:	7318.15.6080
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N MS24694C71 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.407 Inches Minimum
Fastener Length:	1.828 Inches Minimum And 1.875 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.327 Inches Minimum And 0.385 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	85000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Corrosion Resisting
Screw Material Document And Classification:	66 Fed Std Single Material Response
Screw Surface Treatment:	Passivate
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24694C71> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.