

## P/N MS24694C74

## **Description**

Fastener Length: 2-1/16", Thread: 10-32, Thread Length: 13/32

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

### **Additional Information**

#### **Alternate Part Numbers**

MS24694-C74

SKU / Model: MS24694C74

Minimum Qty (MOQ): 25

NSN: 5305-00-824-2007

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS24694C74 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.407 Inches Minimum
Fastener Length:	2.015 Inches Minimum And 2.062 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.327 Inches Minimum And 0.385 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	85000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material Document And Classification:	66 Fed Std Single Material Response
Thread Series Designator:	Unf

## **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/MS24694C74">https://military-fasteners.com/screws/machine+screws/MS24694C74</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/machine+screws/MS24694C74">https://military-fasteners.com/screws/machine+screws/MS24694C74</a> and selecting the quantity you