

Description

Fastener Length: 2-3/16", Thread: 10-32, Thread Length: 13/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS24694C76
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-460-9877
Schedule B:	7318.15.6080
ECCN:	9A991



* See page 2 for technical characteristics

P/N MS24694C76 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.372 Inches Minimum And 0.419 Inches Maximum
Fastener Length:	2.140 Inches Minimum And 2.187 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.371 Inches Minimum And 0.385 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.1900 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	1700 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316
Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24694C76> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.