

Description

corrosion resistant steel, length: 17/32", grip: 9/64", thread: 1/4-28, countersunk, flat head, machine screw, structural

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**

[MS24694-C95](#)

SKU / Model:	MS24694C95
Minimum Qty (MOQ):	50
NSN:	5305-00-051-4134
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS24694C95 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.319 Inches Minimum
Fastener Length:	0.531 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.447 Inches Minimum And 0.507 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	85000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316
Screw Surface Treatment:	Passivate
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24694C95> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.