

Description

Fastener Length: 3-1/8", Thread: 3/8-24, Thread Length: 47/64

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[MS24694-S224](#)

SKU / Model:	MS24694S224
Minimum Qty (MOQ):	5
NSN:	5305-00-079-7974
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS24694S224 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.573 Inches Minimum And 0.734 Inches Maximum
Fastener Length:	3.078 Inches Minimum And 3.125 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.686 Inches Minimum And 0.762 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.375 Inches
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 8740 Or Steel Comp 8630
Screw Material Document And Classification:	Mil-s-6049 Mil Spec 1st Material Response Or Mil-s-6050 Mil Spec 2nd Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24694S224> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.