

Description

length: 23/32, grip: 3/16", thread: 10-32, 100?, countersunk, flat head, cadmium plated steel, structural, MS24694 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[MS24694S-52](#)
[MS24694-S52](#)

SKU / Model:	MS24694S52
Minimum Qty (MOQ):	100
NSN:	5305-00-958-3409
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS24694S52 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.421 Inches Minimum And 0.499 Inches Maximum
Fastener Length:	0.640 Inches Minimum And 0.687 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.327 Inches Minimum And 0.385 Inches Maximum
Head Height:	0.080 Inches Nominal
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 8740 Or Steel Comp 8630
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS24694S52> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.