

**Description**

Stud size 1/4", size 2 awg, red sleeve color, insulated ring terminal, crimp style

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS25036126
Minimum Qty (MOQ):	10
NSN:	5940-00-557-4339
ECCN:	EAR99
National Motor Freight:	061680, Elec Wiring Plugs Etc



# P/N MS25036-126 Specifications

Overall Length:	2.069 Inches
Overall Width:	0.711 Inches
Material Thickness:	0.109 Inches
Maximum Conductor Size Accommodated:	2 Awg
Electrical Insulation Feature:	Insulating Sleeve
Mounting Method Style:	Ring
Mounting Hole Diameter:	0.266 Inches
Mounting Tongue Width:	0.711 Inches
Mounting Facility Thickness:	0.109 Inches
Identification Code Color:	Red
End Item Identification:	W/s: Engine, Aircraft F110-ge-400; Tactical Air Opns Module (an/tyq-23); Generator, 30kw, Diesel, Military Standard Family; Torpedo, Adcap 48; Support Equipment, B-1 Aircraft; Aircraft, (ac-130h, Mc-130h, Ec-130e, Hc-130); Aircraft, C-2a (reprocured); Helicopter, Mh-53e; Test Consoles, Mini-space
Basic Shape Style:	Crimp
Conductor Accommodation Type:	Recessed Barrel Single End
Part Name Assigned By Controlling Agency:	Terminal, Lug Splices, Conductor, Crimp Style, Type Ii, Class 1
Material:	Copper Alloy Overall Except Insulation
Material:	Plastic Polyamide Insulation Or Plastic Vinyl Insulation
Surface Treatment:	Tin Overall Except Insulation Single Layer
Surface Treatment Document And Classification:	Mil-t-10727,ty 2 Mil Spec Single Treatment Response Overall Except Insulation Single Layer

## How to Order

Order this lug terminal from our inventory online by visiting <https://military-fasteners.com/electrical/lug+terminals/MS25036-126> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.