

Description

stud size 3/8", size 2 awg, red sleeve color, insulated ring, crimp style, MS25036 series terminal

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS25036127
Minimum Qty (MOQ):	10
NSN:	5940-00-113-8191
Schedule B:	7415.39.0000
ECCN:	EAR99
National Motor Freight:	061680, Elec Wiring Plugs Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS25036-127 Specifications

Overall Length:	2.069 Inches
Overall Width:	0.689 Inches
Material Thickness:	0.081 Inches
Maximum Conductor Size Accommodated:	2 Awg
Electrical Insulation Feature:	Insulating Sleeve
Mounting Method Style:	Ring
Mounting Hole Diameter:	0.392 Inches
Mounting Tongue Width:	0.689 Inches
Mounting Facility Thickness:	0.081 Inches
Identification Code Color:	Red
Basic Shape Style:	Crimp
Conductor Accommodation Type:	Recessed Barrel Single End
Part Name Assigned By Controlling Agency:	Terminal,lug,crimp Style, Copper, Insulated,ring Tongue,bell Mounthed,t Ype li, Class 1, (for 105mdc Total Conductor Termperture)
Material:	Copper Alloy Overall Except Insulation
Material:	Plastic Polyamide Insulation
Material Document And Classification:	Qq-c-502 Fed Spec 1st Material Response Overall Except Insulation Or Qq-c-576 Fed Spec 2nd Material Response Overall Except Insulation Or Ww-t-799 Fed Spec 3rd Material Response Overall Except Insulation
Surface Treatment:	Tin Overall Except Insulation Single Layer
Surface Treatment Document And Classification:	Mil-t-10727 Mil Spec Single Treatment Response Overall Except Insulation Single Layer

How to Order

Order this lug terminal from our inventory online by visiting <https://military-fasteners.com/electrical/lug+terminals/MS25036-127> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.