

**Description**

Lens color: red, clearance hole: 15/32", without dimmer feature, small indicator light with press to test function, lamp sold separately.

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[800-1030-0331-504](tel:800-1030-0331-504)

|                         |                                   |
|-------------------------|-----------------------------------|
| SKU / Model:            | MS250416                          |
| Minimum Qty (MOQ):      | 1                                 |
| NSN:                    | 6210-00-143-6620                  |
| ECCN:                   | EAR99                             |
| National Motor Freight: | 109700, Lamp Or Lighting Fixtures |



\* See page 2 for technical characteristics

## P/N MS25041-6 Specifications

|  |  |
|--|--|
| <b>Overall Length:</b>                         | 1.750 Inches Maximum   |
| <b>Overall Diameter:</b>                       | 0.650 Inches Maximum   |
| <b>Lamp Base Type Accommodated:</b>            | Midget Flanged   |
| <b>Lamp Bulb Size Designator:</b>              | T-1 3/4  |
| <b>Lens Quantity:</b>                          | 1  |
| <b>Lens Color:</b>                             | Red Single Light 1st Position Horizontal                           |
| <b>Panel Accommodation Hole Diameter:</b>      | 0.469 Inches Nominal   |
| <b>Lens Mounting Method:</b>                   | Screw In   |
| <b>Mounting Method:</b>                        | Panel  |
| <b>Panel Thickness For Which Designed:</b>     | 0.312 Inches Maximum   |
| <b>Features Provided:</b>                      | Press To Test  |
| <b>Lamp Type Accommodated And Quantity:</b>    | 1 Incandescent   |
| <b>Lens Type:</b>                              | Flat, Knurled, Threaded Shank Single Light 1st Position Horizontal |
| <b>Lens Light Transmission Characteristic:</b> | Transparent Single Light 1st Position Horizontal                   |
| <b>Transmitted Legend Color:</b>               | White Single Light 1st Position Horizontal Full Display Division A |
| <b>Lens Legend:</b>                            | 1 Single Light 1st Position Horizontal Full Display Division A     |
| <b>Transmitted Light Color:</b>                | Red Single Light 1st Position Horizontal Full Display Division A   |
| <b>Lens Back Surface Condition:</b>            | Smooth Single Light 1st Position Horizontal                        |
| <b>Lens Face Surface Condition:</b>            | Smooth Single Light 1st Position Horizontal                        |
| <b>Special Features:</b>                       | Press To Test Engraved On Holder                                   |
| <b>Material:</b>                               | Aluminum Body  |
| <b>Surface Treatment:</b>                      | Anodize Body   |
| <b>Style Designator:</b>                       | Round Frame, Round Lens Type                                       |
| <b>Terminal Type And Quantity:</b>             | 3 Solder Lug   |
| <b>Departure From Cited Designator:</b>        | As Modified By Lens Inscription                                    |

## How to Order

Order this indicator light from our inventory online by visiting <https://military-fasteners.com/electrical/indicator+lights/MS25041-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.