

P/N MS25082-C10

Description

Thread Size: 5/8", Nut Height: 1/8", Head Width: 7/8

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

Alternate Part Numbers

MS25082C10

SKU / Model: MS25082C10

Minimum Qty (MOQ): 10

NSN: 5310-01-076-3180

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N MS25082-C10 Specifications

Thread Class:	2b
Thread Direction:	Right-hand
Nut Style:	Hexagon
Nut Height:	0.134 Inches Minimum And 0.144 Inches Maximum
Width Across Flats:	0.812 Inches Minimum And 0.825 Inches Maximum
Thread Series:	Unf
Thread Quantity Per Inch:	18
Nominal Thread Size:	0.625 Inches
Bearing Surface Type:	Chamfered
Material:	Steel Comp 304 Overall Or Steel Comp 304l Overall Or Steel Comp 305 Overall Or Steel Comp 309 Overall Or Steel Comp 310 Overall Or Steel Comp 316 Overall Or Steel Comp 317 Overall Or Steel Comp 321 Overall Or Steel Comp 347 Overall Or Steel Comp 302 Overall
Material Document And Classification:	Qq-s-763 Fed Spec All Material Responses Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Nondefinitive Spec/std Data:	2 Type And 5 Style

How to Order

Order this plain hexagon nut from our inventory online by visiting https://military-fasteners.com/nuts/plain+hexagon+nuts/MS25082-C10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/nuts/plain+hexagon+nuts/MS25082-C10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/nuts/plain+hexagon+nuts/MS25082-C10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/nuts/plain+hexagon+nuts/MS25082-C10 and selecting the quantity of the property of the prope