

Description

a = stud size #4 or # 6, b = stud size #8 or #10, last number indicates length in inches - bonding jumper assembly

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS250832AB6
Minimum Qty (MOQ):	10
NSN:	6150-00-661-0183
National Motor Freight:	062360, Leads / Lead Wires Elec Article Etc

NO IMAGE
AVAILABLE

P/N MS25083-2AB6 Specifications

Cross-sectional Shape Style:	Round
Cross Section Outside Diameter:	0.080 Inches Nominal
Termination Type:	Lug Terminal W/mounting Hole Both Ends Single Conductor
Lead Overall Length:	6.000 Inches Minimum And 6.250 Inches Maximum
Strand Quantity Per Conductor:	7 Single Conductor
Conductor Form:	Stranded Single Conductor
Round Conductor Size:	12 Awg Single Conductor
Strand Awg Size Per Conductor:	37 Single Conductor
Terminal Lug Aperture Size:	0.143 Inches 1st End Single Conductor
Terminal Lug Aperture Size:	0.196 Inches 2nd End Single Conductor
Terminal Manufacturer Identifying Reference Number:	Ms25036-111 1st End Single Conductor
Terminal Manufacturer Identifying Reference Number:	Ms25036-112 2nd End Single Conductor
Terminal Commercial And Government Entity Code:	96906 Both Ends Single Conductor
Lead Pull Strength:	110.0 Pounds
Material:	Copper Core Conductor Single Conductor
Material Document And Classification:	Qq-w-343,soft Fed Std All Material Responses Core Conductor Single Conductor
Surface Treatment:	Tin Core Conductor Third Group
Test Data Document:	96906-ms25083 Standard (includes Industry Or Association Standards, Individual Manufactureer Standards, Etc.).

How to Order

Order this electrical lead from our inventory online by visiting <https://military-fasteners.com/electrical/electrical+leads/MS25083-2AB6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.