

Description

b stud size: #8 or #10, d stud size: 5/16", length: 3", last number indicates length in inches, bonding jumper assembly

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS250832BD3
Minimum Qty (MOQ):	10
NSN:	6150-01-360-7068
ECCN:	EAR99



* See page 2 for technical characteristics

P/N MS25083-2BD3 Specifications

Cross-sectional Shape Style:	Round
Cross Section Outside Diameter:	0.080 Inches Nominal
Termination Type:	Lug Terminal W/mounting Hole Both Ends Single Conductor
Lead Overall Length:	3.000 Inches Minimum And 3.250 Inches Maximum
Strand Quantity Per Conductor:	7 Single Conductor
Conductor Form:	Stranded Single Conductor
Round Conductor Size:	12 Awg Single Conductor
Strand Awg Size Per Conductor:	37 Single Conductor
Terminal Commercial And Government Entity Code:	96906 Both Ends Single Conductor
Lead Pull Strength:	110.0 Pounds
Material:	Copper Core Conductor All Conductors
Material Document And Classification:	Astm B172,soft Assn Std All Material Responses Core Conductor All Conductors
Surface Treatment:	Tin Core Conductor All Conductors

How to Order

Order this electrical lead from our inventory online by visiting <https://military-fasteners.com/electrical/electrical+leads/MS25083-2BD3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.