

Description

stud size #8 or #10, last number indicates length in inches, bonding jumper, MS25083 series lead

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS250835BB7
Minimum Qty (MOQ):	10
NSN:	6150-00-297-3928
ECCN:	EAR99
National Motor Freight:	062360, Leads / Lead Wires Elec Article Etc



P/N MS25083-5BB7 Specifications

Cross-sectional Shape Style:	Round
Cross Section Outside Diameter:	0.080 Inches Nominal
Termination Type:	Lug Terminal W/mounting Hole Both Ends Single Conductor
Lead Overall Length:	7.373 Inches Minimum And 7.623 Inches Maximum
Strand Quantity Per Conductor:	259 Single Conductor
Conductor Form:	Stranded Single Conductor
Round Conductor Size:	12 Awg Single Conductor
Strand Awg Size Per Conductor:	36 Single Conductor
Terminal Lug Aperture Size:	0.196 Inches 1st End Single Conductor
Terminal Lug Aperture Size:	0.196 Inches 2nd End Single Conductor
Lead Pull Strength:	110.0 Pounds
Material:	Copper Core Conductor Single Conductor
Material Document And Classification:	Astm B172,soft Assn Std All Material Responses Core Conductor Single Conductor
Surface Treatment:	Tin Core Conductor Third Group

How to Order

Order this electrical lead from our inventory online by visiting <https://military-fasteners.com/electrical/electrical+leads/MS25083-5BB7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.