

Description

Fastener Length: 57/64", Thread: 8-32, Thread Length: 17/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS250871
Minimum Qty (MOQ):	2
NSN:	5305-00-897-7125
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS25087-1 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.234 Inches Minimum And 0.266 Inches Maximum
Fastener Length:	0.859 Inches Minimum And 0.891 Inches Maximum
Head Style:	Round
Head Diameter:	0.287 Inches Minimum And 0.309 Inches Maximum
Head Height:	0.107 Inches Minimum And 0.120 Inches Maximum
First Diameter From Head:	0.120 Inches Minimum And 0.125 Inches Maximum
Distance From Largest Bearing Surface Of Head To End Of First Diameter:	0.625 Inches Nominal
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Externally Relieved Body Diameter Quantity:	1
Material:	Steel Comp 1010 Overall
Material Document And Classification:	Qq-s-630 Fed Spec Single Material Response Overall Or Qq-s-631 Fed Spec Single Material Response Overall Or Qq-s-634 Fed Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS25087-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.