

P/N MS25089-1F

Description

MS25089-1F Push Switch

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS250891F

Minimum Qty (MOQ):

NSN: 5930-00-501-4957

ECCN: EAR99

National Motor Freight: 061300, Circuit Breaker / Switch Noi



^{*} See page 2 for technical characteristics

P/N MS25089-1F Specifications

Body Style:	Bushing Mounted
Overall Length:	1.375 Inches Maximum
Overall Height:	0.875 Inches Nominal
Overall Width:	0.875 Inches Nominal
Body Diameter:	0.552 Inches Minimum And 0.572 Inches Maximum
Bushing Length:	0.296 Inches Minimum And 0.328 Inches Maximum
Body Length:	0.888 Inches Minimum And 0.920 Inches Maximum
Case Material:	Metal
Actuator Style:	Round
Actuator Diameter:	0.370 Inches Minimum And 0.377 Inches Maximum
Actuator Height:	0.240 Inches Minimum And 0.260 Inches Maximum
Actuator Color:	Black Single Actuator
Maximum Voltage Rating In Volts:	115.0 Ac And 28.0 Dc
Inclosure Type:	Fully Inclosed
Mounting Method:	Threaded Bushing
Features Provided:	Actuator Seal
Thread Quantity Per Inch:	24
Nominal Thread Size:	0.625 Inches
Nonpile-up Contact Arrangement:	1 Pole, Single Throw, Normally Open, Momentary Action Single Switch Unit
_	10.000 Amperes Resistive Dc And 3.000 Amperes Inductive Dc And 3.000 Amperes Lamp Dc And 10.000 Amperes Resistive Ac And 5.000 Amperes Inductive Ac And 3.000 Amperes Lamp Ac
Test Data Document:	81349-mil-s-8805 Specification (includes Engineering Type Bulletins, Brochures, etc., That Reflect Specification Type Data In Specification Format; Excludes Commercial Catalogs, Industry Directories, And Similar Trade Publications, Reflecting General Type Data On Certain Environmental And Performance Requirements And Test Conditions That Are Shown As "typical", "average", "nominal", Etc.).
Thread Series Designator:	Unef
Terminal Type And Quantity:	2 Tab, Solder Lug

How to Order

