

Description

MS25089-4C Push Switch

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--------------------------------------|
| SKU / Model: | MS250894C |
| Minimum Qty (MOQ): | 1 |
| NSN: | 5930-00-504-6223 |
| Schedule B: | 8536.50.9065 |
| ECCN: | EAR99 |
| National Motor Freight: | 061300, Circuit Breaker / Switch Noi |



* See page 2 for technical characteristics

P/N MS25089-4C Specifications

| | |
|---|---|
| Thread Class: | 2b |
| Body Style: | Bushing Mounted |
| Overall Length: | 1.375 Inches Maximum |
| Overall Height: | 0.875 Inches Nominal |
| Overall Width: | 0.875 Inches Nominal |
| Body Diameter: | 0.552 Inches Minimum And 0.572 Inches Maximum |
| Bushing Length: | 0.296 Inches Minimum And 0.328 Inches Maximum |
| Body Length: | 0.888 Inches Minimum And 0.920 Inches Maximum |
| Case Material: | Metal |
| Actuator Style: | Round |
| Actuator Diameter: | 0.370 Inches Minimum And 0.377 Inches Maximum |
| Actuator Height: | 0.240 Inches Minimum And 0.260 Inches Maximum |
| Actuator Color: | Black Single Actuator |
| Maximum Voltage Rating In Volts: | 115.0 Ac And 28.0 Dc |
| End Item Identification: | Missile Minuteman Lgm-30 |
| Inclosure Type: | Fully Inclosed |
| Mounting Method: | Threaded Bushing |
| Features Provided: | Actuator Seal |
| Thread Quantity Per Inch: | 24 |
| Nominal Thread Size: | 0.625 Inches |
| Nonpile-up Contact Arrangement: | 1 Pole, Single Throw, Normally Open, Double Make, Momentary Action, With Contact On Arm Single Switch Unit |
| Contact Load Current Rating At Maximum Rated Voltage: | 10.000 Amperes Resistive Dc And 3.000 Amperes Inductive Dc And 3.000 Amperes Lamp Dc And 10.000 Amperes Resistive Ac And 5.000 Amperes Inductive Ac And 3.000 Amperes Lamp Ac |
| Test Data Document: | 81349-mil-c-8805 Specification (includes Engineering Type Bulletins, Brochures,etc., That Reflect Specification Type Data In Specification Format; Excludes Commercial Catalogs, Industry Directories, And Similar Trade Publications, Reflecting General Type Data On Certain Environmental And Performance Requirements And Test Conditions That Are Shown As "typical", "average", "nominal", Etc.). |
| Thread Series Designator: | Unef |
| Terminal Type And Quantity: | 3 Tab, Solder Lug |

How to Order

Order this push switch from our inventory online by visiting <https://military-fasteners.com/switches/sensitive+switch/MS25089-4C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.