

**Description**

MS25089-4C Push Switch

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS250894C
Minimum Qty (MOQ):	1
NSN:	5930-00-504-6223
Schedule B:	8536.50.9065
ECCN:	EAR99
National Motor Freight:	061300, Circuit Breaker / Switch Noi

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

# P/N MS25089-4C Specifications

<b>Thread Class:</b>	2b
<b>Body Style:</b>	Bushing Mounted
<b>Overall Length:</b>	1.375 Inches Maximum
<b>Overall Height:</b>	0.875 Inches Nominal
<b>Overall Width:</b>	0.875 Inches Nominal
<b>Body Diameter:</b>	0.552 Inches Minimum And 0.572 Inches Maximum
<b>Bushing Length:</b>	0.296 Inches Minimum And 0.328 Inches Maximum
<b>Body Length:</b>	0.888 Inches Minimum And 0.920 Inches Maximum
<b>Case Material:</b>	Metal
<b>Actuator Style:</b>	Round
<b>Actuator Diameter:</b>	0.370 Inches Minimum And 0.377 Inches Maximum
<b>Actuator Height:</b>	0.240 Inches Minimum And 0.260 Inches Maximum
<b>Actuator Color:</b>	Black Single Actuator
<b>Maximum Voltage Rating In Volts:</b>	115.0 Ac And 28.0 Dc
<b>End Item Identification:</b>	Missile Minuteman Lgm-30
<b>Inclosure Type:</b>	Fully Inclosed
<b>Mounting Method:</b>	Threaded Bushing
<b>Features Provided:</b>	Actuator Seal
<b>Thread Quantity Per Inch:</b>	24
<b>Nominal Thread Size:</b>	0.625 Inches
<b>Nonpile-up Contact Arrangement:</b>	1 Pole, Single Throw, Normally Open, Double Make, Momentary Action, With Contact On Arm Single Switch Unit
<b>Contact Load Current Rating At Maximum Rated Voltage:</b>	10.000 Amperes Resistive Dc And 3.000 Amperes Inductive Dc And 3.000 Amperes Lamp Dc And 10.000 Amperes Resistive Ac And 5.000 Amperes Inductive Ac And 3.000 Amperes Lamp Ac
<b>Test Data Document:</b>	81349-mil-c-8805 Specification (includes Engineering Type Bulletins, Brochures,etc., That Reflect Specification Type Data In Specification Format; Excludes Commercial Catalogs, Industry Directories, And Similar Trade Publications, Reflecting General Type Data On Certain Environmental And Performance Requirements And Test Conditions That Are Shown As "typical", "average", "nominal", Etc.).
<b>Thread Series Designator:</b>	Unef
<b>Terminal Type And Quantity:</b>	3 Tab, Solder Lug

## How to Order

Order this push switch from our inventory online by visiting <https://military-fasteners.com/switches/sensitive+switch/MS25089-4C> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.