

Description

battery disconnect, mates with MS3509-28, MS25182 series connector

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS251822
Minimum Qty (MOQ):	1
NSN:	5935-00-686-0447
Schedule B:	8536.69.5050
ECCN:	EAR99
National Motor Freight:	061680, Elec Wiring Plugs Etc



P/N MS25182-2 Specifications

Body Style:	Battery Plug
Overall Length:	4.040 Inches Maximum
Overall Height:	3.700 Inches Nominal
Overall Width:	3.400 Inches Maximum
Environmental Protection:	Chemical Resistant And Salt Water Resistant
Cable Entrance Diameter:	0.900 Inches Nominal
Mating End Quantity:	1
Contact Position Arrangement Style:	2 Single Mating End
Contact Removability:	Nonremovable Single Mating End Single Contact Grouping
Shell Type:	Solid
Connector Locking Method:	Jackscrew
Terminal Location:	Back Single Mating End Single Contact Grouping
Contact Material:	Metal Single Mating End Single Contact Grouping
Insert Material:	Plastic Single Mating End
Terminal Type:	Screw W/wire Lock Single Mating End Single Contact Grouping
Included Contact Quantity:	2 Single Mating End Single Contact Grouping
Included Contact Type:	Round Socket Single Mating End Single Contact Grouping
Test Data Document:	81349-mil-p-18148 Specification (includes Engineering Type Bulletins, Brochures,etc., That Reflect Specification Type Data In Specification Format; Excludes Commercial Catalogs, Industry Directories, And Similar Trade Publications, Reflecting General Type Data On Certain Environmental And Performance Requirements And Test Conditions That Are Shown As "typical", "average", "nominal", Etc.).
Specification/standard Data:	96906-ms25182 Government Standard

How to Order

Order this electrical receptacle connector from our inventory online by visiting <https://military-fasteners.com/electrical/electrical+receptacle+connectors/MS25182-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.