

Description

Length: 1-3/8

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS252532
Minimum Qty (MOQ):	1
NSN:	5930-00-833-5123
National Motor Freight:	061300, Circuit Breaker / Switch Noi

NO IMAGE
AVAILABLE

P/N MS25253-2 Specifications

Body Style:	Hole Mounted
Overall Length:	1.406 Inches Maximum
Center To Center Distance Between Mounting Facilities Parallel To Length:	0.872 Inches Minimum And 0.878 Inches Maximum
Overall Width:	0.415 Inches Maximum
Body Length:	1.079 Inches Minimum And 1.109 Inches Maximum
Body Width:	0.415 Inches Maximum
Body Height:	0.610 Inches Minimum And 0.640 Inches Maximum
Case Material:	Plastic
Unthreaded Mounting Hole Diameter:	0.113 Inches Minimum And 0.116 Inches Maximum
Center To Center Distance Between Mounting Facilities Parallel To Height:	0.403 Inches Minimum And 0.409 Inches Maximum
Actuator Length:	0.105 Inches Minimum And 0.115 Inches Maximum
Actuator Style:	Rectangular
Actuator Height:	0.124 Inches Nominal
Actuator Width:	0.160 Inches Minimum And 0.170 Inches Maximum
Actuator Free Position Height:	0.640 Inches Maximum
Maximum Voltage Rating In Volts:	115.0 Ac And 28.0 Dc
Inclosure Type:	Uninclosed
Mounting Method:	Unthreaded Hole
Nonpile-up Contact Arrangement:	1 Pole, Double Throw, Both Positions Maintained Single Switch Unit
Switch Release Force:	14.0 Ounces Maximum
Switch Actuating Force:	14.0 Ounces Maximum
Actuator Movement:	0.047 Pretravel Inches Maximum And 0.031 Overtravel Inches Minimum And 0.020 Differential Inches Maximum
Contact Load Current Rating At Maximum Rated Voltage:	10.000 Amperes Resistive Dc And 10.000 Amperes Inductive Dc And 6.000 Amperes Motor Dc And 10.000 Amperes Resistive Ac And 10.000 Amperes Inductive Ac And 3.000 Amperes Motor Ac
Test Data Document:	81349-mils8805 Specification (includes Engineering Type Bulletins, Brochures,etc., That Reflect Specification Type Data In Specification Format; Excludes Commercial Catalogs, Industry Directories, And Similar Trade Publications, Reflecting General Type Data On Certain Environmental And Performance Requirements And Test Conditions That Are Shown As "typical", "average", "nominal", Etc.).

How to Order

Order this sensitive switch from our inventory online by visiting <https://military-fasteners.com/electrical/sensitive+switch/MS25253-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.