

Description

25 amp, 28 VDC, threaded mount panel

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[8836K9](#)

SKU / Model:	MS25306222
Minimum Qty (MOQ):	1
NSN:	5930-00-728-4328
ECCN:	EAR99
National Motor Freight:	061300, Circuit Breaker / Switch Noi



P/N MS25306-222 Specifications

Unable To Decode:	Unable To Decode
Body Style:	Bushing Mount
Hazardous Locations/environmental Protection:	Weatherproof
Bushing Length:	0.458 Inches Minimum And 0.478 Inches Maximum
Body Length:	1.336 Inches Maximum
Body Width:	0.734 Inches Maximum
Unthreaded Mounting Hole Diameter:	0.087 Inches Minimum
Actuator Style:	Round
Actuator Diameter:	0.237 Inches Minimum And 0.243 Inches Maximum
Actuator Height:	0.655 Inches Minimum And 0.719 Inches Maximum
Actuator Position-action Relationship:	Up Position Maintained And Down Position Maintained
Maximum Voltage Rating In Volts:	115.0 Ac And 28.0 Dc
End Item Identification:	Missile Minuteman Lgm-30
Mounting Surface To Terminal End Distance:	1.250 Inches Maximum
Inclosure Type:	Fully Inclosed
Mounting Method:	Unthreaded Hole
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.469 Inches
Nonpile-up Contact Arrangement:	1 Pole, Single Throw, Both Positions Maintained Single Switch Unit
Contact Load Current Rating At Maximum Rated Voltage:	25.000 Amperes Resistive Dc And 15.000 Amperes Inductive Dc And 7.000 Amperes Motor Dc And 25.000 Amperes Resistive Ac And 15.000 Amperes Inductive Ac And 7.000 Amperes Motor Ac
Thread Series Designator:	Uns
Terminal Type And Quantity:	2 Screw

How to Order

Order this toggle switch from our inventory online by visiting <https://military-fasteners.com/switches/toggle+switches/MS25306-222> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.