

Description

Fastener Length: 43/64", Thread: 10-32, Thread Length: 1/2", screw and washer assembly, MS25332 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS253321
Minimum Qty (MOQ):	5
NSN:	5305-00-910-5363
Schedule B:	7318.15.2091
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS25332-1 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.406 Inches Minimum And 0.500 Inches Maximum
Fastener Length:	0.662 Inches Minimum And 0.682 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.302 Inches Minimum And 0.322 Inches Maximum
Head Height:	0.057 Inches Minimum And 0.067 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Screw Material:	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 303se
Screw Material Document And Classification:	Mil-s-7720 Mil Spec 1st Material Response Or Astm A582 Assn Std 2nd Material Response Or Astm A582 Assn Std 3rd Material Response
Screw Surface Treatment:	Passivate
Special Features:	N0. 4-40 Unc 2b Driled And Tapped Hole 0.375 In. Deep From Drive End,furnished W/three Flat Washers An960c10l 0.032 In. Thk
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS25332-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.