

Description

Fastener Length: 43/64", Thread: 10-32, Thread Length: 1/2", screw and washer assembly, MS25332 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS253321 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5305-00-910-5363 |
| Schedule B: | 7318.15.2091 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N MS25332-1 Specifications

| | |
|--|---|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.406 Inches Minimum And 0.500 Inches Maximum |
| Fastener Length: | 0.662 Inches Minimum And 0.682 Inches Maximum |
| Head Style: | Flat Chamfer |
| Head Diameter: | 0.302 Inches Minimum And 0.322 Inches Maximum |
| Head Height: | 0.057 Inches Minimum And 0.067 Inches Maximum |
| Internal Drive Style: | Slot |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Screw Material: | Steel Comp 302 Or Steel Comp 303 Or Steel Comp 303se |
| Screw Material Document And Classification: | Mil-s-7720 Mil Spec 1st Material Response Or Astm A582 Assn Std 2nd Material Response Or Astm A582 Assn Std 3rd Material Response |
| Screw Surface Treatment: | Passivate |
| Special Features: | N0. 4-40 Unc 2b Driled And Tapped Hole 0.375 In. Deep From Drive End,furnished W/three Flat Washers An960c10l 0.032 In. Thk |
| Thread Series Designator: | Unf |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS25332-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.