

Description

MS25361-60 Circuit Breaker

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS2536160
Minimum Qty (MOQ):	1
NSN:	5925-00-881-2463
ECCN:	EAR99
National Motor Freight:	061300, Circuit Breaker / Switch Noi



NO IMAGE
AVAILABLE

P/N MS25361-60 Specifications

Body Style:	Single Pole Type
Bushing Length:	0.250 Inches Nominal
Body Length:	2.189 Inches Maximum
Body Width:	0.750 Inches Maximum
Case Material:	Metal
Center To Center Distance Between Terminals Parallel To Length:	1.438 Inches Nominal
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:	1.812 Inches Nominal
Fragility Factor:	Moderately Rugged
Mounting Surface To Terminal End Distance:	2.250 Inches Nominal
Pole Quantity:	1
Mounting Facility Type And Quantity:	2 Threaded Hole
Storage Type:	General Purpose Warehouse
Thread Quantity Per Inch:	32
Maximum Continuous Load Current Rating Per Pole:	60.0 Amperes Ac Single Location And 60.0 Amperes Dc Single Location
Operating Voltage Type And Rating Per Pole In Volts:	200.0 Ac Single Location And 28.0 Dc Single Location
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:	3500.0 Ac Single Location And 6000.0 Dc Single Location
Circuit Protection Type:	Overcurrent Single Location
Trip Release Method:	Thermal Single Location
Trip Release Characteristic:	Time Delay Single Location
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:	138.0 Single Location
Reset Method:	Manual
Main Contact Tripping Mechanism Type:	Trip Free
Manual Actuator Type And Quantity:	1 Push-pull

Actuator Function:	Trip-reset
Actuator Position Designation:	At Pole One
Internal Trip Release Configuration:	Series Trip Single Location
Nominal Thread Size:	0.138 Inches
Trip Delay Time In Seconds Per Rated Continuous Current:	15.000 Minimum At 200 Pct Single Location And 65.000 Maximum At 200 Pct Single Location
Inclosure Protection Type For Which Designed:	Moisture Resistant And Explosion Resistant
Trip Release Ambient Temp Rating:	25.0 Deg Celsius Nominal Single Location
Frequency In Hertz:	400.0 Single Location
Unpackaged Unit Weight:	5.000 Ounces
Test Data Document:	81349-mil-c-5809 Specification (includes Engineering Type Bulletins, Brochures,etc., That Reflect Specification Type Data In Specification Format; Excludes Commercial Catalogs, Industry Directories, And Similar Trade Publications, Reflecting General Type Data On Certain Environmental And Performance Requirements And Test Conditions That Are Shown As "typical", "average", "nominal", Etc.).
Thread Series Designator:	Unc
Terminal Type And Quantity:	2 Tab W/screw
Specification/standard Data:	96906-ms25361 Government Standard

How to Order

Order this circuit breaker from our inventory online by visiting <https://military-fasteners.com/electrical/circuit+breakers/MS25361-60> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.