



★ FASTENERS

Military-Fasteners.com

P/N MS27039-0804

Description

length: 0.281", grip: 0.032", thread: 8-32, pan head structural, cadmium plated steel, MS27039 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS270390804
Minimum Qty (MOQ):	100
NSN:	5305-00-903-7707
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS27039-0804 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.140 Inches Minimum And 0.281 Inches Maximum
Fastener Length:	0.266 Inches Minimum And 0.313 Inches Maximum
Head Style:	Pan
Head Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Screw Material:	Steel Comp 8630 Or Steel Comp 4037
Screw Surface Treatment:	Cadmium And Chromate
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS27039-0804> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.