

Description

Fastener Length: 2-5/16", Thread: 8-32, Thread Length: 31/64", MS27039 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS270390836
Minimum Qty (MOQ):	50
NSN:	5305-01-268-9485
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093483, Bolts,nuts Or Screws,noi Iron Or



* See page 2 for technical characteristics

P/N MS27039-0836 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.407 Inches Minimum And 0.484 Inches Maximum
Fastener Length:	2.266 Inches Minimum And 2.313 Inches Maximum
Head Style:	Pan
Head Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Screw Material:	Steel Comp 4037 Or Steel Comp 8630
Screw Material Document And Classification:	Ams6300 Assn Std 1st Material Response Or Mil-s-6050 Mil Spec 2nd Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS27039-0836> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.