

Description

Fastener Length: 2-5/16", Thread: 8-32, Thread Length: 31/64", MS27039 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--|
| SKU / Model: | MS270390836 |
| Minimum Qty (MOQ): | 50 |
| NSN: | 5305-01-268-9485 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093483, Bolts,nuts Or Screws,noi Iron Or |



P/N MS27039-0836 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.407 Inches Minimum And 0.484 Inches Maximum |
| Fastener Length: | 2.266 Inches Minimum And 2.313 Inches Maximum |
| Head Style: | Pan |
| Head Diameter: | 0.306 Inches Minimum And 0.322 Inches Maximum |
| Head Height: | 0.105 Inches Minimum And 0.115 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.164 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 125000 Pounds Per Square Inch |
| Hardness Rating: | 26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum |
| Screw Material: | Steel Comp 4037 Or Steel Comp 8630 |
| Screw Material Document And Classification: | Ams6300 Assn Std 1st Material Response Or Mil-s-6050 Mil Spec 2nd Material Response |
| Screw Surface Treatment: | Cadmium And Chromate |
| Screw Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unc |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS27039-0836> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.