

Description

Fastener Length: 2-7/8", Thread: 10-32, Thread Length: 13/32", MS27039 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS27039145
Minimum Qty (MOQ):	20
NSN:	5305-00-764-7946
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS27039-1-45 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.407 Inches Minimum
Fastener Length:	2.829 Inches Minimum And 2.876 Inches Maximum
Head Style:	Pan No. 2
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Screw Material:	Steel Comp 4037 Or Steel Comp 8630
Screw Material Document And Classification:	Ams 6300 Assn Std 1st Material Response Or Mil-s-6050 Mil Spec 2nd Material Response
Screw Surface Treatment:	Cadmium
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS27039-1-45> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.