



★ FASTENERS

Military-Fasteners.com

P/N MS27039-4-14

Description

length: 0.906", grip: 0.375", thread: 1/4-28, pan head, structural, cadmium plated steel, MS27039 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS27039414
Minimum Qty (MOQ):	100
NSN:	5305-00-082-5113
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS27039-4-14 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.531 Inches Minimum
Fastener Length:	0.906 Inches Nominal
Head Style:	Pan
Head Diameter:	0.473 Inches Minimum And 0.492 Inches Maximum
Head Height:	0.162 Inches Minimum And 0.175 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Screw Material:	Steel
Screw Surface Treatment:	Cadmium And Chromate
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS27039-4-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.