

# P/N MS27039-4-31

### **Description**

Fastener Length: 1-31/32", Thread: 1/4-28, Thread Length: 1/2", MS27039 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS27039431

Minimum Qty (MOQ): 25

NSN: 5305-00-600-3006

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









# P/N MS27039-4-31 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.531 Inches Nominal
Fastener Length:	1.969 Inches Nominal
Head Style:	Pan
Head Diameter:	0.473 Inches Minimum And 0.492 Inches Maximum
Head Height:	0.162 Inches Minimum And 0.175 Inches Maximum
Internal Drive Style:	Cross Recess Type Ii
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Screw Material:	Steel Comp 4037
Screw Material Document And Classification:	Mil-s-8695 Mil Spec Single Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unf

## **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/MS27039-4-31">https://military-fasteners.com/screws/machine+screws/MS27039-4-31</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/machine+screws/MS27039-4-31">https://military-fasteners.com/screws/machine+screws/MS27039-4-31</a> and selecting the quantity you