

Description

Fastener Length: 2-3/16", Thread: 1/4-28, Thread Length: 37/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS27039434
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-869-4095
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS27039-4-34 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.501 Inches Minimum And 0.578 Inches Maximum
Fastener Length:	2.141 Inches Minimum And 2.188 Inches Maximum
Head Style:	Pan
Head Diameter:	0.473 Inches Minimum And 0.492 Inches Maximum
Head Height:	0.162 Inches Minimum And 0.175 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Screw Material:	Steel Comp 4037 Or Steel Comp 8630
Screw Material Document And Classification:	Ams 6300 Assn Std 1st Material Response Or Mil-s-6050 Mil Spec 2nd Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 3 Fed Spec All Treatment Responses
Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS27039-4-34> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.