

Description

Fastener Length: 2-1/4", Thread: 1/4-28, Thread Length: 37/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS27039435
Minimum Qty (MOQ):	10
NSN:	5305-00-936-4592
Schedule B:	7318.15.4000
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS27039-4-35 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.501 Inches Minimum And 0.578 Inches Maximum
Fastener Length:	2.204 Inches Minimum And 2.251 Inches Maximum
Head Style:	Pan
Head Diameter:	0.473 Inches Minimum And 0.492 Inches Maximum
Head Height:	0.162 Inches Minimum And 0.175 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Screw Material:	Steel Comp 4037 Or Steel Comp 8630
Screw Material Document And Classification:	Ams 6300 Assn Std 1st Material Response Or Mil-s-6050 Mil Spec 2nd Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS27039-4-35> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.