

Description

Fastener Length: 2-7/16", Thread: 1/4-28, Thread Length: 37/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS27039438
Minimum Qty (MOQ):	15 EA
NSN:	5305-01-023-6202
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS27039-4-38 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.499 Inches Minimum And 0.578 Inches Maximum
Fastener Length:	2.391 Inches Minimum And 2.438 Inches Maximum
Head Style:	Pan No. 2
Head Diameter:	0.473 Inches Minimum And 0.492 Inches Maximum
Head Height:	0.162 Inches Minimum And 0.175 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Screw Material:	Steel Comp 1340 Or Steel Comp 4037
Screw Material Document And Classification:	Mils-16974 Mil Spec Single Material Response Or Mil-s-8695 Mil Spec Single Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-46,ty 2,cl 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS27039-4-38> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.