

Description

Fastener Length: 2-13/16", Thread: 1/4-28, Thread Length: 37/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS27039444
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-102-4552
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS27039-4-44 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.501 Inches Minimum And 0.578 Inches Maximum
Fastener Length:	2.766 Inches Minimum And 2.813 Inches Maximum
Head Style:	Modified Pan
Head Diameter:	0.375 Inches Nominal
Head Height:	0.098 Inches Minimum And 0.108 Inches Maximum
Grip Diameter:	0.2460 Inches Minimum And 0.2490 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.250 Inches
Grip Length:	2.235 Inches Minimum And 2.265 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Yield Strength:	125000 Pounds Per Square Inch
Material:	Steel Comp 4037 Overall
Material Document And Classification:	Ams6300 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS27039-4-44> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.