

Description

Fastener Length: 45/64", Thread: 1/4-24, Thread Length: 5/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS27039510 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5305-00-526-0508 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N MS27039-5-10 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.548 Inches Minimum And 0.625 Inches Maximum |
| Fastener Length: | 0.657 Inches Minimum And 0.704 Inches Maximum |
| Head Style: | Pan |
| Head Diameter: | 0.594 Inches Minimum And 0.615 Inches Maximum |
| Head Height: | 0.203 Inches Minimum And 0.218 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.312 Inches |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 125000 Pounds Per Square Inch |
| Hardness Rating: | 26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum |
| Screw Material: | Steel Comp 4037 Or Steel Comp 8630 |
| Screw Material Document And Classification: | Ams 6300 Assn Std 1st Material Response Or Mil-s-6050 Mil Spec 2nd Material Response |
| Screw Surface Treatment: | Cadmium And Chromate |
| Screw Surface Treatment Document And Classification: | Qq-p-416 Ty 2,cl 3 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unf |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS27039-5-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.