

**Description**

Fastener Length: 59/64", Thread: 1/4-24, Thread Length: 9/16", MS27039 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS27039514
Minimum Qty (MOQ):	10
NSN:	5305-00-086-6993
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N MS27039-5-14 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.578 Inches Minimum
<b>Fastener Length:</b>	0.922 Inches Nominal
<b>Head Style:</b>	Pan
<b>Head Diameter:</b>	0.594 Inches Minimum And 0.615 Inches Maximum
<b>Head Height:</b>	0.203 Inches Minimum And 0.218 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.312 Inches
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	125000 Pounds Per Square Inch
<b>Hardness Rating:</b>	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
<b>Screw Material:</b>	Steel
<b>Screw Surface Treatment:</b>	Cadmium And Chromate
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS27039-5-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.