

**Description**

Fastener Length: 2-5/64", Thread: 1/4-24, Thread Length: 5/8

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS27039532
Minimum Qty (MOQ):	5
NSN:	5305-01-270-2709
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N MS27039-5-32 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.538 Inches Minimum And 0.625 Inches Maximum
<b>Fastener Length:</b>	2.032 Inches Minimum And 2.079 Inches Maximum
<b>Head Style:</b>	Pan
<b>Head Diameter:</b>	0.594 Inches Minimum And 0.615 Inches Maximum
<b>Head Height:</b>	0.203 Inches Minimum And 0.218 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.312 Inches
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	125000 Pounds Per Square Inch
<b>Screw Material:</b>	Steel Comp 4037 Or Steel Comp 8630
<b>Screw Material Document And Classification:</b>	Mil-s-8695 Mil Spec 1st Material Response Or Mil-s-6050 Mil Spec 2nd Material Response
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS27039-5-32> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.