

Description

Fastener Length: 31/64", Thread: 1/2-20, Thread Length: 31/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS27039806 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5305-00-570-8736 |
| Schedule B: | 7318.15.2010 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N MS27039-8-06 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.438 Inches Minimum And 0.485 Inches Maximum |
| Fastener Length: | 0.438 Inches Minimum And 0.485 Inches Maximum |
| Head Style: | Pan No. 2 |
| Head Diameter: | 0.958 Inches Minimum And 0.987 Inches Maximum |
| Head Height: | 0.327 Inches Minimum And 0.348 Inches Maximum |
| Internal Drive Style: | Cross Recess Type Ii |
| Nominal Thread Diameter: | 0.500 Inches |
| Thread Quantity Per Inch: | 20 |
| Minimum Tensile Strength: | 125000 Pounds Per Square Inch |
| Hardness Rating: | 26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum |
| Screw Material: | Steel Comp 8630 Or Steel Comp 4037 |
| Screw Material Document And Classification: | Mil-s-6050 Mil Spec 1st Material Response Or Mil-s-8695 Mil Spec 2nd Material Response |
| Screw Surface Treatment: | Cadmium |
| Screw Surface Treatment Document And Classification: | Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unf |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS27039-8-06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.