

**Description**

Fastener Length: 5/16", Thread: 8-32, Thread Length: 9/32", MS27039 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[MS27039-C0804](#)

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS27039C0804                              |
| Minimum Qty (MOQ):      | 50  |
| NSN:                    | 5305-00-136-5563                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N MS27039C0804 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>  | 3a  |
| <b>Thread Direction:</b>                                    | Right-hand                                    |
| <b>Thread Length:</b>                                       | 0.202 Inches Minimum And 0.281 Inches Maximum |
| <b>Fastener Length:</b>                                     | 0.266 Inches Minimum And 0.313 Inches Maximum |
| <b>Head Style:</b>  | Pan   |
| <b>Head Diameter:</b>                                       | 0.306 Inches Minimum And 0.322 Inches Maximum |
| <b>Head Height:</b>   | 0.105 Inches Minimum And 0.115 Inches Maximum |
| <b>Internal Drive Style:</b>                                | Cross Recess Type 1                           |
| <b>Nominal Thread Diameter:</b>                             | 0.164 Inches                                  |
| <b>Thread Quantity Per Inch:</b>                            | 32  |
| <b>Minimum Tensile Strength:</b>                            | 125000 Pounds Per Square Inch                 |
| <b>Screw Material:</b>                                      | Iron Alloy 660                                |
| <b>Screw Material Document And Classification:</b>          | Ams 5732 Assn Std Single Material Response    |
| <b>Screw Surface Treatment:</b>                             | Passivate                                     |
| <b>Screw Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response    |
| <b>Thread Series Designator:</b>                            | Unc   |

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS27039C0804> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.