

**Description**

corrosion resistant steel - length: 0.344", grip: 0.032", thread: 8-32, pan head structural machine screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[MS27039C08-05](#) [MS27039-C0805](#)

SKU / Model:	MS27039C0805
Minimum Qty (MOQ):	50
NSN:	5305-00-113-3732
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N MS27039C0805 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.297 Inches Minimum And 0.376 Inches Maximum
<b>Fastener Length:</b>	0.329 Inches Minimum And 0.376 Inches Maximum
<b>Head Style:</b>	Pan
<b>Head Diameter:</b>	0.306 Inches Minimum And 0.322 Inches Maximum
<b>Head Height:</b>	0.105 Inches Minimum And 0.115 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	125000 Pounds Per Square Inch
<b>Screw Material:</b>	Iron Alloy 660
<b>Screw Material Document And Classification:</b>	Ams 5732 Assn Std Single Material Response
<b>Screw Surface Treatment:</b>	Passivate
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS27039C0805> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.