

**Description**

length: 0.406", grip: 0.032", thread: 8-32, corrosion resistant steel, pan head structural, MS27039 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[MS27039C08-06](#)

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS27039C0806                              |
| Minimum Qty (MOQ):      | 50  |
| NSN:                    | 5305-00-944-8272                          |
| Schedule B:             | 7318.15.2091                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N MS27039C0806 Specifications

|  |   |
|--|---|
| <b>Thread Class:</b>                               | 3a  |
| <b>Thread Direction:</b>                           | Right-hand                                    |
| <b>Thread Length:</b>                              | 0.329 Inches Minimum And 0.376 Inches Maximum |
| <b>Fastener Length:</b>                            | 0.391 Inches Minimum And 0.438 Inches Maximum |
| <b>Head Style:</b>                                 | Pan   |
| <b>Head Diameter:</b>                              | 0.306 Inches Minimum And 0.322 Inches Maximum |
| <b>Head Height:</b>                                | 0.105 Inches Minimum And 0.115 Inches Maximum |
| <b>Internal Drive Style:</b>                       | Cross Recess Type 1                           |
| <b>Nominal Thread Diameter:</b>                    | 0.164 Inches                                  |
| <b>Thread Quantity Per Inch:</b>                   | 32  |
| <b>Minimum Tensile Strength:</b>                   | 125000 Pounds Per Square Inch                 |
| <b>Screw Material:</b>                             | Iron Alloy 660                                |
| <b>Screw Material Document And Classification:</b> | Ams 5732 Assn Std Single Material Response    |
| <b>Screw Surface Treatment:</b>                    | Passivate                                     |
| <b>Thread Series Designator:</b>                   | Unc   |

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS27039C0806> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.