



★ FASTENERS

Military-Fasteners.com

P/N MS27039C0809

Description

length: 0.594", grip: 0.156", thread: 8-32, pan head structural, corrosion resistant steel, MS27039 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS27039C0809
Minimum Qty (MOQ):	25
NSN:	5305-00-977-9052
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS27039C0809 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.346 Inches Minimum And 0.485 Inches Maximum
Fastener Length:	0.579 Inches Minimum And 0.626 Inches Maximum
Head Style:	Pan
Head Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams 5735 Assn Std Single Material Response
Screw Surface Treatment:	Passivate
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS27039C0809> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.