

## P/N MS27039C0820

## **Description**

Fastener Length: 1-5/16", Thread: 8-32, Thread Length: 31/64

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

#### **Alternate Part Numbers**

#### MS27039C08-20

SKU / Model: MS27039C0820

Minimum Qty (MOQ): 10

NSN: 5305-00-925-7874

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS27039C0820 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.345 Inches Minimum And 0.484 Inches Maximum
Fastener Length:	1.266 Inches Minimum And 1.313 Inches Maximum
Head Style:	Pan
Head Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams 5735 Assn Std Single Material Response
Screw Surface Treatment:	Passivate
Thread Series Designator:	Unc

## **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/MS27039C0820">https://military-fasteners.com/screws/machine+screws/MS27039C0820</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/machine+screws/MS27039C0820">https://military-fasteners.com/screws/machine+screws/MS27039C0820</a> and selecting the quantity you