

**Description**

Fastener Length: 1-13/16", Thread: 8-32, Thread Length: 31/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS27039C0828
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-003-9287
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS27039C0828 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.407 Inches Minimum And 0.484 Inches Maximum
<b>Fastener Length:</b>	1.766 Inches Minimum And 1.813 Inches Maximum
<b>Head Style:</b>	Pan
<b>Head Diameter:</b>	0.306 Inches Minimum And 0.322 Inches Maximum
<b>Head Height:</b>	0.105 Inches Minimum And 0.115 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	125000 Pounds Per Square Inch
<b>Screw Material:</b>	Iron Alloy 660 Or Steel Comp 302
<b>Screw Surface Treatment:</b>	Passivate
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS27039C0828> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.