

Description

length: 0.281", grip: 0.032", thread: 10-32, pan head structural, corrosion resistant steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS27039C104
Minimum Qty (MOQ):	50
NSN:	5305-00-925-9678
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS27039C1-04 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.234 Inches Minimum And 0.281 Inches Maximum
Fastener Length:	0.266 Inches Minimum And 0.313 Inches Maximum
Head Style:	Pan No. 2
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Screw Material:	Iron Alloy 660
Screw Surface Treatment:	Passivate
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS27039C1-04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.