

Description

length: 0.906", grip: 0.438", thread: 10-32, pan head, structural, corrosion resistant steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS27039C114 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5305-00-928-1629 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N MS27039C1-14 Specifications

| | |
|----------------------------------|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.438 Inches Minimum And 0.515 Inches Maximum |
| Fastener Length: | 0.891 Inches Minimum And 0.938 Inches Maximum |
| Head Style: | Pan No. 2 |
| Head Diameter: | 0.357 Inches Minimum And 0.373 Inches Maximum |
| Head Height: | 0.122 Inches Minimum And 0.133 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 125000 Pounds Per Square Inch |
| Screw Material: | Iron Alloy 660 |
| Screw Surface Treatment: | Passivate |
| Thread Series Designator: | Unf |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS27039C1-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.