



★ FASTENERS

Military-Fasteners.com

P/N MS27039C1-17

Description

length: 1.094", grip: 0.625", thread: 10-32, pan head, structural, corrosion resistant steel, MS27039 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS27039C117
Minimum Qty (MOQ):	25
NSN:	5305-00-022-3072
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS27039C1-17 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.439 Inches Minimum And 0.516 Inches Maximum
Fastener Length:	1.079 Inches Minimum And 1.126 Inches Maximum
Head Style:	Pan
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams 5732 Assn Std Single Material Response
Screw Surface Treatment:	Passivate
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS27039C1-17> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.