



Military-Fasteners.com

P/N MS27039C1-34

Description

Fastener Length: 2-3/16", Thread: 10-32, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS27039C134
Minimum Qty (MOQ):	15 EA
NSN:	5305-00-197-2399
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS27039C1-34 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.438 Inches Minimum And 0.515 Inches Maximum
Fastener Length:	2.141 Inches Minimum And 2.188 Inches Maximum
Head Style:	Pan
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams 5732 Assn Std Single Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS27039C1-34> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.