

Description

Fastener Length: 13/16", Thread: 1/4-28, Thread Length: 37/64

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS27039C412
Minimum Qty (MOQ):	20
NSN:	5305-00-932-3964
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS27039C4-12 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.430 Inches Minimum And 0.578 Inches Maximum
Fastener Length:	0.766 Inches Minimum And 0.813 Inches Maximum
Head Style:	Pan
Head Diameter:	0.473 Inches Minimum And 0.492 Inches Maximum
Head Height:	0.162 Inches Minimum And 0.175 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams 5735 Assn Std Single Material Response
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS27039C4-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.